



CARPORT PHOTOVOLTAIC

IBIS - Sandwich panels

Welded and bolted structural steelwork protected with hot-dip galvanization, with "N" shaped support columns complete of base plate and accessories.
Material S235JR-S275JR-S355JR UNI EN 10025-1/2, grade 8.8 bolting material.

DELIVERY TIME: 3 WEEKS FROM EXW ORDER

VALIDITY PRICES FROM 04-2023 TO 12-2023



€ 0.00 VAT EXCLUDED

TECHNICAL SPECIFICATIONS

Dimensions	10,00x5,00 m	Metal Working	Galvanized, pre-painted, shaped metal sheets for ridges, corner joints, flashings and eaves and any other necessary element.
Square Meters	50 m ²	Painting	Hot-dip galvanized coating UNI EN ISO 1461:2009.
Useful height	2,00 m	Covering	Roof in sandwich panels consisting of two galvanised sheet layers filled with an inner core of polyurethane foam (PUR).
Step columns	5,00 m	Photovoltaic	Inverter power 6 Kw. Photovoltaic system installed on no. 2 canopy modules.
Wind	25 m/s		
Antiseismic	YES		
Covering	Sandwich panels		

OPTIONAL PRODUCTS

EV CHARGING STATION

EV charging station with no. 2 socket outlet, floor standing, connected to the user's distribution network (optimizable with PV), complete with access badge reader, power 7kW, 32 A.

COLOR STRUCTURE

galvanization

Other colors depending on availability. The colours here shown are purely indicative and may result different in reality.

COLOR COVERING



ral 8017



ral 3009



ral 6005



ral 5010



ral 9006



ral 9002

Other colors depending on availability. The colours here shown are purely indicative and may result different in reality.